Canon

Delighting You Always

SOUTH & SOUTHEAST ASIA **REGIONAL HEADOUARTERS**

Canon Singapore Pte. Ltd. 1 HarbourFront Avenue #04-01 Keppel Bay Tower Singapore 098632 Tel: 65-6799-8888 Fax: 65-6799-8882

www.canon-asia.com

CANON OFFICES

HONG KONG Canon Hongkong Co., Ltd. Tel : 852-3191-2388 Fax: 852-2369-3800 www.canon.com.hk

INDIA Canon India Pvt. Ltd. Tel : 91-124-4160-000 Fax : 91-124-4160-011 www.canon.co.in

MALAYSIA Canon Marketing (Malaysia) Sdn. Bhd. Tel : 603-7844-6000 Fax : 603-7845-0505 www.canon.com.my

PHILIPPINES Canon Marketing (Philippines), Inc. Tel : 632-884-9000 Fax : 632-894-4174 www.canon.com.ph

SINGAPORE Canon Singapore Pte. Ltd. Tel : 65-6799-8888 Fax : 65-6799-8882 www.canon.com.sg

THAILAND Canon Marketing (Thailand) Co., Ltd. Tel : 66-2-3449-999 Fax : 66-2-3449-967/68 www.canon.co.th

VIETNAM Canon Marketing Vietnam Co., Ltd. Ho Chi Minh City, Vietnam Tel : 84-8 38200 466 Fax : 84-8 38200 477 www.canon.com.vn

CANON BUSINESS PARTNERS

BANGLADESH J.A.N Associates Tel : 880-2-8611-444 Fax: 880-2-8610-410

BRUNEI Interhouse Company Tel: 673-2-6530-01 Fax: 673-2-6530-03

CAMBODIA i-Qlick (Cambodia) Pte. Ltd. Tel : 855-23-966-638 Fax: 855-23-996-639

Royal Cambodia Co., Ltd Tel : 855-23-4289-55 Fax : 855-23-7229-61

INDONESIA P.T. Samafitro Tel : 62-21-3455-521 Fax : 62-21-3844-271

MALDIVES SIMDI Company (Pvt) Ltd. Tel : 960-3334-421 Fax : 960-3334-424

MYANMAR Mvanmar Golden Rock International Co., Ltd. Tel : 95-1-202092/3/4 Fax : 95-1-202079

NEPAL International Electronics Concern (P) Ltd. Tel : 977-1-4421-991 Fax : 977-1-4421-909

PAKISTAN MBM International Tel : 9221-3227-0933 Fax : 9221-3438-6308

SRI LANKA Metropolitan Communications (Pvt) Ltd. Tel : 94-11-2437-797 Fax : 94-11-2448-980

ADVANCED ALL-IN-ONE WITH WI-FI

imageCLASS

MF4720w

MULTI-FUNCTION MONOCHROME LASER PRINTER



DEALER'S STAMP

0168W735 © 2012 Canon Singapore Pte. Ltd. All rights reserved.

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any ability or contractual obligations with respect to this document.



FOR THE WIRELESS HOME OFFICE

Combining innovative design and simple one-touch simplicity, the new imageCLASS MF4720w is the ideal companion for the wireless home or home office.



The Vari-Angle Operation Panel affords an excellent view of the LCD display at any time, while wireless device setup is assisted by the beautiful push-button simplicity of WPS technology. And with the new Quiet Mode feature, you can be sure the imageCLASS MF4720w will always get the job done without disturbing others in the vicinity.



FEATURES & PERFORMANCE



Canon

^{5 line} Extend the panel out towards you, or flushed against the front profile for a better viewing experience. A large 5-line LCD display shows more menu options at any time.

🗢 COPY / 🍃 SCAN

Report 🏵 Menu

Paper Status Mon Setting Cancel



< OK ►


23

Black

device into near-stealth operation, reducing engine noise to a bare minimum.

QUICK WARM-UP AND RECOVERY TIMES

With On Demand Fixing technology, users can expect the imageCLASS MF4720w to resume a ready-state in just 2 seconds, ready for the next print or copy job.



WIFE WIRELESS IEE802.11n COMPLIANT WITH WI-FI PROTECTED SETUP

Wireless IEEE802.11n compliance and Wi-Fi Protected Setup (WPS) allows fuss-free wireless device integration into secured wireless networks. Wired LAN is also available as a standard.

∙€FCopy

SETUP

ONE-TOUCH SOLUTION KEYS

Three task-dedicated Solution Keys on the imageCLASS MF4720w further simplify operations with minimal button-pushing for the most standard of tasks.

// Scan To PC 1 & PC 2 Two user-defined keys that remember your preferred scan settings when scanning to a computer.

II Paper Save Copy Reduces the number of steps needed to make paper-saving copies, such as 2-on-1 or 4-on-1 copies.

LASER QUALITY PRINTING AND COPYING

With laser quality print and copy speed up to 23ppm/cpm (A4), and First Printout Time at 6 seconds (A4) or less, the imageCLASS MF4720w will complete your multi-page print or copy jobs faster than conventional inkjet systems.

SUPERB PRINT PROCESSING EFFICIENCY

Canon's next-generation UFRII LT page description language enables faster print processing using a unique Load Balancing System between the host PC and device.



The imageCLASS MF4720w consumes a mere

1.4W* in Standby mode. With image layout

options such 2-on-1 and 4-on-1 copying, you

can save the environment while reducing

INCREDIBLE ENERGY SAVINGS

paper costs. (*Wired connection only)

MULTI-FUNCTION MONOCHROME LASER PRINTER

Cartridge 328 GENUINE



MINIMAL DEVICE MAINTENANCE

The Canon All-in-One Toner Cartridge 328 combines the photosensitive drum, toner reservoir, and waste toner container into a compact and precisely-engineered unit, making toner replacements easy and minimizes device maintenance.

QUALITY TONER ENGINEERING

Canon MS-Toner adopts a unique spherical shape to achieve smooth and consistent imaging quality. MS-Toner also improves melting performance, which complements and enhances the On-Demand Fixing process through the use of less heat and pressure.

MF4720W | Specifications | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | ..

| PRINT | |
|---|--|
| | Manasharmalaan |
| Printing Method | Monochrome Laser |
| Print Speed (Simplex; A4/LTR) | Up to 23/24ppm (pages per minute) |
| Print Resolution | 600 x 600dpi |
| Print Quality with Image Refinement Technology | 1200 (equivalent) x 600dpi |
| Warm-up Time (From Power On) | 13.5 secs or less |
| Recovery Time (From Sleep Mode) | Approx. 2.0 secs. |
| First Printout Time (FPOT) | Approx. 6/5.8 secs (A4/LTR) |
| Print Language | UFR II LT |
| Print Margins | 5 mm-top, bottom, left and right (Other sizes than Envelope) 10 mm-top, bottom, left and right (Envelope) |
| Print Features | Watermark, Page Composer, Toner Saver |
| COPY | |
| Copy Speed (Simplex; A4/LTR) | Up to 23/24cpm (copies per minute) |
| Copy Resolution | 600 x 600dpi |
| First Copy Time (FCOT) | Approx. 9.0/8.7 secs (A4/LTR) |
| Maximum Number of Copies | Up to 99 copies |
| Reduce/Enlargement | 25 - 400% in 1% increments |
| Copy Features | Memory Sort, 2 on 1, 4 on 1, ID Card Copy |
| SCAN | |
| SCAN | |
| SCAN Scan Resolution | Optical: Up to 600 x 600dpi Driver Enhanced: Up to 9600 x 9600dpi |
| | |
| Scan Resolution | Driver Enhanced: Up to 9600 x 9600dpi |
| Scan Resolution Color Depth | Driver Enhanced: Up to 9600 x 9600dpi 24-bit |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features PAPER HANDLING | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network TWAIN, WIA (Scan Driver Compatibility) Plain Paper (60-80g/m ²): 250-sheet Cassette, |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features PAPER HANDLING Paper Input (Standard) | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network TWAIN, WIA (Scan Driver Compatibility) Plain Paper (60-80g/m²): 250-sheet Cassette, 1-sheet Multipurpose Tray |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features PAPER HANDLING Paper Input (Standard) Paper Output Paper Sizes | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network TWAIN, WIA (Scan Driver Compatibility) Plain Paper (60-80g/m ²): 250-sheet Cassette, 1-sheet Multipurpose Tray 100 sheets (face down , 20lb LTR / 68g/m ² A4) A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features PAPER HANDLING Paper Input (Standard) Paper Output Paper Sizes (Standard Cassette) Paper Sizes | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network TWAIN, WIA (Scan Driver Compatibility) Plain Paper (60-80g/m ²): 250-sheet Cassette, 1-sheet Multipurpose Tray 100 sheets (face down , 20lb LTR / 68g/m ² A4) A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 210mm to Max. 216 x 356 mm) A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, |
| Scan Resolution Color Depth Pull Scan Push Scan (Scan to PC) with MF ToolBox Scan Features PAPER HANDLING Paper Input (Standard) Paper Output Paper Sizes (Standard Cassette) Paper Sizes (Multipurpose Tray) | Driver Enhanced: Up to 9600 x 9600dpi 24-bit Yes, USB and network Yes, USB and network TWAIN, WIA (Scan Driver Compatibility) Plain Paper (60-80g/m ²): 250-sheet Cassette, 1-sheet Multipurpose Tray 100 sheets (face down , 20lb LTR / 68g/m ² A4) A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 210mm to Max. 216 x 356 mm) A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127mm to Max. 216 x 356 mm) Plain, Heavy, Recycled, Transparency, Label, |

| CONNECTIVITY AND SOFTWARE | |
|--|--|
| Standard Interface/s (Wired) | USB 2.0 High-Speed, 10/100 Base-T Ethernet (Network) |
| Standard Interface/s (Wireless) | Wi-Fi 802.11b/g/n (Infrastructure mode, WPS easy setup) |
| Network Protocol | Print: LPD, RAW, WSD-Print (IPv4, IPv6) Scan: WSD-Scan (IPv4, IPv6) TCP/IP Application Services: Bonjour (mDNS), DHCP, BOOTP, RARP, Auto IP (IPv4), DHCPv6 (IPv6) Management: SNMPv1 (IPv4, IPv6) |
| Network Security (Wired) | IP/Mac address filtering |
| Network Security (Wireless) | WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), 802.1x (LEAP, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS) |
| One-Push Wireless Configuration | Wi-Fi Protected Setup (WPS) |
| Operating System Compatibility | Windows@7 (32/64-bit) Windows@XP (32/64-bit) Windows@Vista (32/64-bit) Windows@ Server 2008 R2 (32/64-bit)(*1) Windows@ Server 2003 (32/64-bit)(*1) Windows@ Server 2003 (32/64-bit)(*1) Mac OS X 10.4.9 & up (*2) Linux (*3) |
| Software Included | Printer driver, Scanner driver, MF Toolbox, Presto! PageManager, SSID Tool |
| | ······································ |
| GENERAL SPECIFICATIONS | |
| GENERAL SPECIFICATIONS | 128MB |
| | |
| Memory | 128MB |
| Memory LCD Display | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) |
| Memory LCD Display Dimensions (W x D x H) | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened) 10.0kg (without cartridge) |
| Memory LCD Display Dimensions (W x D x H) Weight | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened) 10.0kg (without cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) Maximum: 1320W or less During Operation: Approx. 560W (Average; Copying) During Standby: Approx. 3.5W |
| Memory LCD Display Dimensions (W x D x H) Weight Power Consumption | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened) 10.0kg (without cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) Maximum: 1320W or less During Operation: Approx. 560W (Average; Copying) During Standby: Approx. 3.5W During Standby: Approx. 1.4W / 2.4W (Wireless) During Operation: Sound Pressure Level (Bystander's position): 50dB in Printing (reference value) Sound Power Level: 6.5B in Printing During Standby: Sound Pressure Level (Bystander's position): Inaudible (reference value) (*5) |
| Memory LCD Display Dimensions (W x D x H) Weight Power Consumption Noise Levels (*4) | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened) 10.0kg (without cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) Maximum: 1320W or less During Operation: Approx. 560W (Average; Copying) During Standby: Approx. 3.5W During Sleep: Approx. 1.4W / 2.4W (Wireless) During Operation: Sound Pressure Level (Bystander's position): 50dB in Printing (reference value) Sound Power Level: 6.5B in Printing During Standby: Sound Pressure Level (Bystander's position): Inaudible (reference value) (*5) Sound Power Level: 4.3B or less Temperature: 10 to 30°C |
| Memory LCD Display Dimensions (W x D x H) Weight Power Consumption Noise Levels (*4) Operating Environment | 128MB 5-line BW LCD (Vari-Angle Operation Panel) 390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened) 10.0kg (without cartridge) 10.5kg (with cartridge) 10.5kg (with cartridge) Maximum: 1320W or less During Operation: Approx. 560W (Average; Copying) During Standby: Approx. 3.5W During Operation: Sound Pressure Level (Bystander's position): 50urd Pressure Level (Bystander's position): Sound Pressure Level (Bystander's position): Sound Pressure Level (Bystander's position): Sound Pressure Level (Bystander's position): Inaudible (reference value) (*5) Sound Pressure Level (Bystander's position): Inaudible (reference value) (*5) Sound Power Level: 4.3B or less Temperature: 10 to 30°C Humidity: 20% to 80% RH (no condensation) |

*1 ScanGear and MF Toolbox are not available for Windows Server 2003/2008. *2 The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available. *3 Only the print function is supported for Linux. The latest drivers for Linux can be downloaded from www.canon-asia.com when available, *4 Tested in accordance to IS07779 and declared per IS09296. *5 "Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value (about background noise IS0 7779. *6 Toner cartridge yield in accordance with IS0/IEC 19752. *7 Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.